

**Description**

Fastener Length: 37/64", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS2833T4PTY
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-507-4818
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS2833T4PTY Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.558 Inches Minimum And 0.588 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.280 Inches Minimum And 0.337 Inches Maximum
<b>Grip Diameter:</b>	0.162 Inches Minimum And 0.163 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Features Provided:</b>	Cetyl Alcohol Lubricant
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams4971 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2833T4PTY> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.