

Description

Fastener Length: 37/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS2833T4PTY |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5305-01-507-4818 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS2833T4PTY Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 0.558 Inches Minimum And 0.588 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.280 Inches Minimum And 0.337 Inches Maximum |
| Grip Diameter: | 0.162 Inches Minimum And 0.163 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Features Provided: | Cetyl Alcohol Lubricant |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams4971 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2833T4PTY> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.