

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS2835C13DT
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-365-0397
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS2835C13DT Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.235 Inches Minimum And 1.265 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.577 Inches Minimum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal Overall
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.068 Inches Nominal First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas2835 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2835C13DT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.