

Description

Fastener Length: 1-25/64", Thread: 5/16-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS2835C15DT
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-467-7474
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS2835C15DT Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.361 Inches Minimum And 1.391 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.490 Inches Nominal
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	C-17a Aircraft
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Item Has Drilled Shank At The Threaded End, And The Distance From End To Shank Hole Center Is 0.172 Inch Min., 0.192 Inch Max; The Diameter Of The Hole Is 0.076 Inch Min., 0.086 Inch Max.
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2835C15DT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.