

Description

Fastener Length: 1-25/64", Thread: 5/16-24, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS2835C15DT     |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5305-01-467-7474 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | 9A991            |



\* See page 2 for technical characteristics

## P/N NAS2835C15DT Specifications

|                                                       |                                                                                                                                                                                             |
|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                                                                                                                                                          |
| <b>Thread Direction:</b>                              | Right-hand                                                                                                                                                                                  |
| <b>Thread Length:</b>                                 | 0.438 Inches Nominal                                                                                                                                                                        |
| <b>Fastener Length:</b>                               | 1.361 Inches Minimum And 1.391 Inches Maximum                                                                                                                                               |
| <b>Head Style:</b>                                    | Flat Countersunk                                                                                                                                                                            |
| <b>Head Diameter:</b>                                 | 0.490 Inches Nominal                                                                                                                                                                        |
| <b>Grip Diameter:</b>                                 | 0.3110 Inches Minimum And 0.3120 Inches Maximum                                                                                                                                             |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                                                                                                                                                               |
| <b>End Item Identification:</b>                       | C-17a Aircraft                                                                                                                                                                              |
| <b>Nominal Thread Diameter:</b>                       | 0.3125 Inches                                                                                                                                                                               |
| <b>Grip Length:</b>                                   | 0.928 Inches Minimum And 0.948 Inches Maximum                                                                                                                                               |
| <b>Thread Quantity Per Inch:</b>                      | 24                                                                                                                                                                                          |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                                                                                                                              |
| <b>Special Features:</b>                              | Item Has Drilled Shank At The Threaded End, And The Distance From End To Shank Hole Center Is 0.172 Inch Min., 0.192 Inch Max; The Diameter Of The Hole Is 0.076 Inch Min., 0.086 Inch Max. |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall                                                                                                                                                           |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Overall                                                                                                                                          |
| <b>Surface Treatment:</b>                             | Passivate Overall                                                                                                                                                                           |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall                                                                                                                                          |
| <b>Thread Series Designator:</b>                      | Unjf                                                                                                                                                                                        |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2835C15DT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.