

Description

Fastener Length: 1-25/64", Thread: 5/16-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS2835C15DT |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-467-7474 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS2835C15DT Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Nominal |
| Fastener Length: | 1.361 Inches Minimum And 1.391 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.490 Inches Nominal |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| End Item Identification: | C-17a Aircraft |
| Nominal Thread Diameter: | 0.3125 Inches |
| Grip Length: | 0.928 Inches Minimum And 0.948 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Special Features: | Item Has Drilled Shank At The Threaded End, And The Distance From End To Shank Hole Center Is 0.172 Inch Min., 0.192 Inch Max; The Diameter Of The Hole Is 0.076 Inch Min., 0.086 Inch Max. |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2835C15DT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.