

Description

Fastener Length: 1-5/16", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS2835C21T |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-446-1457 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS2835C21T Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Nominal |
| Fastener Length: | 1.302 Inches Minimum And 1.322 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.577 Inches Minimum And 0.635 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | Torque-set Ribbed |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.735 Inches Minimum And 1.765 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas2835 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2835C21T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.