

## P/N NAS2852C1NT

### **Description**

Fastener Length: 3/8", Thread: 8-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS2852C1NT
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-476-2599
Schedule B:	7318.15.8085

9A991



ECCN:

<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS2852C1NT Specifications**

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.385 Inches Nominal
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.2534 Inches Minimum And 0.2612 Inches Maximum
Head Height:	0.050 Inches Nominal
Grip Diameter:	0.1621 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	F-16 Aircraft
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.062 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas2852 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS2852C1NT">https://military-fasteners.com/bolts/machine+bolts/NAS2852C1NT</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.