

**Description**

Fastener Length: 3/8", Thread: 8-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS2852C1NT
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-476-2599
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS2852C1NT Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.385 Inches Nominal
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.2534 Inches Minimum And 0.2612 Inches Maximum
<b>Head Height:</b>	0.050 Inches Nominal
<b>Grip Diameter:</b>	0.1621 Inches Minimum And 0.1635 Inches Maximum
<b>Internal Drive Style:</b>	Offset Cruciform (torque Set)
<b>End Item Identification:</b>	F-16 Aircraft
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Grip Length:</b>	0.062 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas2852 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS2852C1NT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.