

## **P/N NAS333CP7**

### **Description**

Fastener Length: 15/16", Thread: 10-32, Thread Length: 11/32

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS333CP7

Minimum Qty (MOQ): 10

NSN: 5305-00-558-3721

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS333CP7 Specifications**

3a
Right-hand
0.344 Inches Minimum
0.891 Inches Minimum And 0.937 Inches Maximum
Flat Countersunk
0.376 Inches Minimum And 0.385 Inches Maximum
0.1885 Inches Minimum And 0.1894 Inches Maximum
0.070 Inches Nominal First Hole
Cross Recess Type 1
0.190 Inches
0.500 Inches Nominal
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
100.0 Degrees Minimum
0.767 Inches Nominal First Hole
32.0 Microinches Top Of Head
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Unf
80205-nas333 Professional/industrial Association Standard

## **How to Order**

