

# **P/N NAS333CPA21-5**

### **Description**

Fastener Length: 2-15/64", Thread: 10-32, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS333CPA215

Minimum Qty (MOQ): 20 EA

NSN: 5305-01-342-9435

Schedule B: 7318.15.8085

ECCN: 9A991



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS333CPA21-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.463 Inches Minimum And 0.489 Inches Maximum
Fastener Length:	2.203 Inches Minimum And 2.249 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.376 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1894 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.802 Inches Minimum And 1.822 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS333CPA21-5">https://military-fasteners.com/screws/close+tolerance+screws/NAS333CPA21-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS333CPA21-5">https://military-fasteners.com/screws/close+tolerance+screws/NAS333CPA21-5</a> and selecting the quantity you