

P/N NAS333CPA5-5

Military-Fasteners.com

#### Description

Fastener Length: 45/64", Thread: 10-32, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

### **Additional Information**

SKU / Model:	NAS333CPA55
Minimum Qty (MOQ):	115 EA
NSN:	5305-00-551-8144
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS333CPA5-5 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.380 Inches Minimum And 0.447 Inches Maximum
Fastener Length:	0.702 Inches Minimum And 0.749 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.376 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1894 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas333 Professional/industrial Association Standard

# How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/close+tolerance+screws/NAS333CPA5-5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.