

P/N NAS334CP23

Description

Fastener Length: 2-7/16", Thread: 1/4-28, Thread Length: 1/2", NAS334 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS334CP23


Minimum Qty (MOQ): 10

NSN: 5305-00-819-6547

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N NAS334CP23 Specifications

	_	
Thread Class:	3a	
Thread Direction:	Right-hand	
Thread Length:	0.443 Inches Minimum And 0.510 Inches Maximum	
Fastener Length:	2.391 Inches Minimum And 2.438 Inches Maximum	
Head Style:	Flat Countersunk	
Head Diameter:	0.497 Inches Minimum And 0.507 Inches Maximum	
Grip Diameter:	0.2483 Inches Minimum And 0.2492 Inches Maximum	
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole	
Single Shear Strength:	4650 Pounds Per Square Inch	
Internal Drive Style:	Cross Recess Type 1	
Nominal Thread Diameter:	0.250 Inches	
Grip Length:	1.928 Inches Minimum And 1.948 Inches Maximum	
Thread Quantity Per Inch:	28	
Minimum Tensile Strength:	160000 Pounds Per Square Inch	
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall	
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum	
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.240 Inches Minimum First Hole And 2.260 Inches Maximum First Hole	
Surface Finish:	32.0 Microinches Grip	
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall	
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall	
Surface Treatment:	Cadmium Overall And Chromate Overall	
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	
Thread Series Designator:	Unf	
Specification/standard Data:	80205-nas334 Professional/industrial Association Standard	

How to Order

uantity you want then click "add to cart". Once items are in y	your cart you can check out <u>here</u> to complete your order.
	Provided by Military-Fasteners.com