

**P/N NAS334CPA13-5** 

Military-Fasteners.com

#### Description

Fastener Length: 1-1/2", Thread: 1/4-28, Thread Length: 1/2

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

### **Additional Information**

SKU / Model:	NAS334CPA135
Minimum Qty (MOQ):	100
NSN:	5305-00-531-0441
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS334CPA13-5 Specifications

Thread Class:3aThread Direction:Right-handThread Length:0.443 Inches Minimum And 0.510 Inches MaximumFastener Length:1.453 Inches Minimum And 1.500 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.497 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.493 Inches Minimum And 0.2492 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:0.990 Inches Minimum And 1.010 Inches MaximumThread Quantity Per Inch:28
Thread Length:0.443 Inches Minimum And 0.510 Inches MaximumFastener Length:1.453 Inches Minimum And 1.500 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.497 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesO.990 Inches Minimum And 1.010 Inches Maximum
Fastener Length:1.453 Inches Minimum And 1.500 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.497 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 Inches0.990 Inches Minimum And 1.010 Inches Maximum
Head Diameter:0.497 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 Inches0.990 Inches Minimum And 1.010 Inches Maximum
Grip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:0.990 Inches Minimum And 1.010 Inches Maximum
Internal Drive Style: Cross Recess Type 1   Nominal Thread Diameter: 0.250 Inches   Grip Length: 0.990 Inches Minimum And 1.010 Inches Maximum
Nominal Thread Diameter:   0.250 Inches     Grip Length:   0.990 Inches Minimum And 1.010 Inches Maximum
Grip Length: 0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Par Inch. 28
Minimum Tensile Strength: 160000 Pounds Per Square Inch
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish: 32.0 Microinches Grip
Material:     Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740       Overall     Overall
Material Document AndMil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rdClassification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:
Thread Series Designator: Unf
Specification/standard Data: 80205nas334 Professional/industrial Association Standard

# How to Order

Order this close tolerance bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS334CPA13-5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.