

P/N NAS334CPA20

Military-Fasteners.com

#### Description

Fastener Length: 2-1/16", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS334CPA20
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-558-4952
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS334CPA20 Specifications

······································	
Thread Length: 0.443 Inches Min	
-	
Fastener Length:2.015 Inches Min	nimum And 0.510 Inches Maximum
	nimum And 2.062 Inches Maximum
Head Style: Flat Countersun	ĸ
Head Diameter: 0.497 Inches Min	nimum And 0.507 Inches Maximum
Grip Diameter: 0.2483 Inches M	linimum And 0.2492 Inches Maximum
Single Shear Strength: 4650 Pounds Pe	r Square Inch
Internal Drive Style: Cross Recess Ty	pe 1
Nominal Thread Diameter: 0.250 Inches	
Grip Length: 1.552 Inches Min	nimum And 1.572 Inches Maximum
Thread Quantity Per Inch: 28	
Minimum Tensile Strength: 160000 Pounds	Per Square Inch
Hardness Rating: 36.0 Rockwell C	Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle: 99.0 Degrees Mi	nimum And 101.0 Degrees Maximum
Surface Finish: 32.0 Microinche	s Grip
Material: Steel Comp 414 Overall	0 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740
	pec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd se Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment: Cadmium Overa	ll And Chromate Overall
Surface Treatment Document And Classification:	class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unf	
Specification/standard Data: 80205-nas334 P	rofessional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS334CPA20</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.