

P/N NAS334CPA23

Military-Fasteners.com

Description

Fastener Length: 2-7/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS334CPA23
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-889-3108
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS334CPA23 Specifications

Thread Class:3aThread Direction:Right-handThread Length:0.443 Inches Minimum And 0.510 Inches MaximumFastener Length:2.391 Inches Minimum And 2.438 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.376 Inches Minimum And 0.385 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 Inches0.250 InchesMinimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square Inch	
Thread Length:0.443 Inches Minimum And 0.510 Inches MaximumFastener Length:2.391 Inches Minimum And 2.438 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.376 Inches Minimum And 0.385 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 Inches0.250 Inches1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:1.6000 Pounds Per Square Inch	
Fastener Length:2.391 Inches Minimum And 2.438 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.376 Inches Minimum And 0.385 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:16000 Pounds Per Square Inch	
Head Style:Flat CountersunkHead Diameter:0.376 Inches Minimum And 0.385 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:16000 Pounds Per Square Inch	
Head Diameter:0.376 Inches Minimum And 0.385 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:16000 Pounds Per Square Inch	
Grip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 Inches0.250 Inches1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:1.6000 Pounds Per Square Inch	
Single Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:16000 Pounds Per Square Inch	
Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:16000 Pounds Per Square Inch	
Nominal Thread Diameter:0.250 InchesGrip Length:1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square Inch	
Grip Length:1.928 Inches Minimum And 1.948 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square Inch	
Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch	
Minimum Tensile Strength: 160000 Pounds Per Square Inch	
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall	
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum	
Surface Finish: 32.0 Microinches Grip	
Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Overall	
Material Document AndMil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rdClassification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall	
Surface Treatment: Cadmium Overall And Chromate Overall	
Surface Treatment Document And Classification:	
Thread Series Designator: Unf	
Specification/standard Data: 80205-nas333 Professional/industrial Association Standard	

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS334CPA23</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.