

P/N NAS334CPA24

Military-Fasteners.com

Description

Fastener Length: 2-9/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS334CPA24
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-616-2531
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS334CPA24 Specifications

Thread Direction:Right-handThread Length:0.443 Inches Minimum And 0.510 Inches MaximumFastenr Length:0.443 Inches Minimum And 2.562 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.497 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4500 Pounds Per Square InchInternal Drive Style:Cross Reces Type 1Nominal Thread Diameter:0.250 Inches0.250 Inches2.052 Inches Minimum And 2.072 Inches MaximumThread Quantity Per Inch:28Countersink Angle:0.900 Pounds Per Square InchMinimum Tensile Strength:160000 Pounds Per Square InchMardness Rating:0.60 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:9.00 Pegrees Minimum And 10.10 Degrees MaximumSurface Finish:3.00 Microinches GripMaterial Document AndMils-5626 Mils Spec 1 st Material Response Overall Or Mils-5000 Mil Spec 2nd Material Response Overall Or Mils-8503 Mil Spec 3rdSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Pocument AndQr.p-416.type 2.class 3 Fed Spec Single Treatment Response Overall Or Mils-6049 Mil Spec 5th Material Response OverallSurface Treatment:Grip-1416.type 2.class 3 Fed Spec Single Treatment Response OverallSurface Treatment:Grip-1416.type 2.class 3 Fed Spec Single Treatment Response Overall		
Thread Length:0.43 Inches Minimum And 0.510 Inches MaximumFastener Length:2.515 Inches Minimum And 2.562 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.497 Inches Minimum And 0.507 Inches MaximumOrip Diameter:0.497 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesO.250 InchesMinimum And 2.072 Inches MaximumMinimum Tensile Strength:160000 Pounds Per Square InchInternal Drive Style:0.500 InchesGrip Diameter:0.250 InchesOunds Per Square Inch160000 Pounds Per Square InchMinimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 2.072 Inches Maximum OverallOuntersink Angle:9.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial:32.0 Microinches GripMaterial:Surface String:Surface Treatment And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6009 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3nd Material Response Overall Or Mil-s-6049 Mil Spec 3th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-604	Thread Class:	3a
Pastener Length:2.515 Inches Minimum And 2.562 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.497 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumInternal Drive Style:Cross Recess Type 1Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 Inches0.250 Inches2.052 Inches MaximumGrip Length:2.052 Inches Minimum And 2.072 Inches MaximumThread Quartity Per Inch:28Minimum Tensile Strength:16000 Pounds Per Square InchMinimum Tensile Strength:0.6000 Pounds Per Square InchMartinal Countersink Angle:9.0 Degrees Minimum And 10.0 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial Pocument AndNil-s-5626 Mill Spec 1st Material Response Overall Or Mil-s-5000 Mill Spec 2nd Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6034 Mil Spec 3th Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Materi	Thread Direction:	Right-hand
Head Style:Flat CountersunkHead Diameter:0.497 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4550 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 Inches0.250 Inches0.250 Inches MaximumThread Quantity Per Inch:2.50 Inches Maximum And 2.072 Inches MaximumThread Quantity Per Inch:80.000 Pounds Per Square Inch8Hardness Rating:0.6000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 10.10 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial Document AndMil-s-5626 Mil Spec 1 st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416.type 2,class 3 Fed Spec Single Treatment Response Overall Or Mil-s-6049 Mil Spec Sth Material Response OverallSurface Treatment Document And Classification:Q-p-416.type 2,class 3 Fed Spec Single Treatment Response OverallThread Series Designator:Un	Thread Length:	0.443 Inches Minimum And 0.510 Inches Maximum
Head Diameter:0.497 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:2.502 Inches Minimum And 2.072 Inches MaximumThread Quantity Per Inch:28Boilton Diameter:0.6000 Pounds Per Square InchMinimum Tensile Strength:16000 Pounds Per Square InchGuartity Per Inch:28Boilton Diameter:0.6000 Pounds Per Square InchCountersink Angle:9.0 Degrees Minimum And 10.0 Degrees Maximum OverallCountersink Angle:9.0 Degrees Minimum And 10.1 Degrees MaximumSurface Finish:2.0 Microinches GripSurface Fraement:Seel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-60	Fastener Length:	2.515 Inches Minimum And 2.562 Inches Maximum
Grip Diameter:0.2483 Inches Minimum And 0.2492 Inches MaximumSingle Shear Strength:4550 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:2.052 Inches Minimum And 2.072 Inches MaximumThread Quantity Per Inch:2Biomon Tensile Strength:6.0000 Pounds Per Square InchMinimum Tensile Strength:6.0000 Pounds Per Square InchBiomon Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:9.0 Degrees Minimum And 10.10 Degrees MaximumSurface Finish:2.0 Microinches GripSurface Finish:2.0 Microinches GripMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Mil-s-6303 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6303 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6303 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6303 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6303 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6303 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6303 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6303 Mil Spec 4th Material Response Overall Or Mil-s-6303 Mil Spec 4th <br< th=""><th>Head Style:</th><td>Flat Countersunk</td></br<>	Head Style:	Flat Countersunk
Single Shear Strength:4650 Pounds Per Square InchInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:2.052 Inches Minimum And 2.072 Inches MaximumThread Quantity Per Inch:8Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.60 Rockwell C Minimum And 10.0 Rockwell C Maximum OverallCountersink Angle:9.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec Sth Mat	Head Diameter:	0.497 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.250 InchesGrip Length:2.052 Inches Minimum And 2.072 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 10.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 10.10 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 overallMaterial Document And Classification:Mils-S626 Mil Spec 1st Material Response Overall Or Mil-s-6009 Mil Spec 4th Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:op-p416,type 2,class 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Grip Diameter:	0.2483 Inches Minimum And 0.2492 Inches Maximum
Nominal Thread Diameter:0.250 InchesGrip Length:2.052 Inches Minimum And 2.072 Inches MaximumThread Quantity Per Inch:8Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:6.0.000 Pounds Per Square InchGountersink Angle:9.0.0 Degrees Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:9.0.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:3.0. Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Re	Single Shear Strength:	4650 Pounds Per Square Inch
Grip Length:2.052 Inches Minimum And 2.072 Inches MaximumThread Quantity Per Inch:36Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:90.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:20.0 Microinches GripMaterial:Stel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-6308 Mil Spec 4th Material Response Overall Or Mil-s-6304 Mil Spec 3th Material Response Overall Or Mil-s-63098 Mil Spec 4th Material Response Overall Or Mil-s-6304 Mil Spec 3th Material Response Overall Or Mil-s-63098 Mil Spec 4th Material Response Overall Or Mil-s-63049 Mil Spec 5th Material Response Overall Or Mil-s-63098 Mil Spec 4th Material Response Overall Or Mil-s-63049 Mil Spec 5th Material Response Overall Or Mil-s-63098 Mil Spec 4th Material Response Overall Or Mil-s-63049 Mil Spec 5th Material Response Overall Or Mil-s-63098 Mil Spec 4th Material Response Overall Or Mil-s-63049 Mil Spec 5th Material Response Overall Or Mil-s-63098 Mil Spec 4th Material Response Overall Or Mil-s-63049 Mil Spec 5th Material Response Overall Or Mil-s-63098 Mil Spec 4th Material Response Overall Or Mil-s-63049 Mil Spec 5th Material Response Overall Or Mil-s-63049 Mil Spec	Internal Drive Style:	Cross Recess Type 1
Thread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallSurface Treatment Document And Classification:Mi-s-16049 Single Treatment Response Overall	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall Og-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Grip Length:	2.052 Inches Minimum And 2.072 Inches Maximum
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:cadmium Overall And Chromate OverallSurface Treatment Document And Classification:q-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallOutputUnf	Thread Quantity Per Inch:	28
Countersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:q-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallOutputMil-set Spec Single Treatment Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallUnfUnf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Classification:Surface Treatment Document And Classification:q-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallMaterial Response Document And Classification:Unf	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallMaterial Response Document And Classification:Unf	Surface Finish:	32.0 Microinches Grip
Classification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Material:	
Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Material Document And Classification:	
Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas334 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas334 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/NAS334CPA24</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.