

## P/N NAS334CPA31

## **Description**

Fastener Length: 3-3/16", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS334CPA31

Minimum Qty (MOQ): 15 EA

NSN: 5305-00-558-3661

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS334CPA31 Specifications**

3a
Right-hand
0.443 Inches Minimum And 0.510 Inches Maximum
3.141 Inches Minimum And 3.188 Inches Maximum
Flat Countersunk
0.497 Inches Minimum And 0.507 Inches Maximum
0.2483 Inches Minimum And 0.2492 Inches Maximum
Cross Recess Type 1
0.250 Inches
2.678 Inches Minimum And 2.698 Inches Maximum
28
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
32.0 Microinches Grip
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Unf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS334CPA31">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS334CPA31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.