

P/N NAS334CPA6-5

Description

Fastener Length: 55/64", Thread: 1/4-28, Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS334CPA65

Minimum Qty (MOQ): 25

NSN: 5305-00-558-2787

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS334CPA6-5 Specifications

| 3a |
|---|
| Right-hand |
| 0.443 Inches Minimum And 0.510 Inches Maximum |
| 0.827 Inches Minimum And 0.874 Inches Maximum |
| Flat Countersunk |
| 0.497 Inches Minimum And 0.507 Inches Maximum |
| 0.2483 Inches Minimum And 0.2492 Inches Maximum |
| Cross Recess Type 1 |
| 0.250 Inches |
| 0.364 Inches Minimum And 0.384 Inches Maximum |
| 28 |
| 160000 Pounds Per Square Inch |
| 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| 32.0 Microinches Grip |
| Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall |
| Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Cadmium Overall And Chromate Overall |
| Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| line |
| Unf |
| |

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS334CPA6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.