

## **P/N NAS335CP16**

## **Description**

Fastener Length: 1-55/64", Thread: 1/4-24, Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS335CP16

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-559-9024

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS335CP16 Specifications

3a
Right-hand
0.505 Inches Minimum And 0.572 Inches Maximum
1.827 Inches Minimum And 1.874 Inches Maximum
Flat Countersunk
0.625 Inches Minimum And 0.635 Inches Maximum
0.3108 Inches Minimum And 0.3117 Inches Maximum
0.076 Inches Nominal First Hole
Cross Recess Type 1
0.312 Inches
1.302 Inches Minimum And 1.322 Inches Maximum
24
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
1.661 Inches Minimum First Hole And 1.681 Inches Maximum First Hole
32.0 Microinches Grip
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Unf
80205-nas335 Professional/industrial Association Standard

## **How to Order**

