

P/N NAS335CPA11

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 9/16", NAS335 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS335CPA11

Minimum Qty (MOQ): 20

NSN: 5305-00-576-2828

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS335CPA11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.505 Inches Minimum And 0.572 Inches Maximum
Fastener Length:	1.203 Inches Minimum And 1.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.625 Inches Minimum And 0.635 Inches Maximum
Grip Diameter:	0.3108 Inches Minimum And 0.3117 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS335CPA11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS335CPA11 and selecting the