



Military-Fasteners.com

P/N NAS335CPA23

Description

Fastener Length: 2-1/2", Thread: 1/4-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS335CPA23
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-827-6547
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS335CPA23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.505 Inches Minimum And 0.572 Inches Maximum
Fastener Length:	2.453 Inches Minimum And 2.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.625 Inches Minimum And 0.635 Inches Maximum
Grip Diameter:	0.3108 Inches Minimum And 0.3117 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.928 Inches Minimum And 1.948 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS335CPA23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.