

**Description**

Fastener Length: 55/64", Thread: 1/4-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS335CPA6
Minimum Qty (MOQ):	100 EA
NSN:	5305-01-458-1962
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

## P/N NAS335CPA6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.531 Inches Nominal
<b>Fastener Length:</b>	0.828 Inches Minimum And 0.874 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.625 Inches Minimum And 0.635 Inches Maximum
<b>Grip Diameter:</b>	0.3108 Inches Minimum And 0.3117 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.312 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Fed Spec 1st Material Response Overall Or Mil-s-8844 Fed Spec 2nd Material Response Overall Or Ams6414 Assn Std 2nd Material Response Overall Or Mil-s-6049 Fed Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas335 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS335CPA6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.