

Description

Fastener Length: 55/64", Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS335CPA6
Minimum Qty (MOQ):	100 EA
NSN:	5305-01-458-1962
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N NAS335CPA6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.531 Inches Nominal
Fastener Length:	0.828 Inches Minimum And 0.874 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.625 Inches Minimum And 0.635 Inches Maximum
Grip Diameter:	0.3108 Inches Minimum And 0.3117 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.312 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Fed Spec 1st Material Response Overall Or Mil-s-8844 Fed Spec 2nd Material Response Overall Or Ams6414 Assn Std 2nd Material Response Overall Or Mil-s-6049 Fed Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas335 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS335CPA6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.