

P/N NAS335CPA7-5

Military-Fasteners.com

Description

Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS335CPA75
Minimum Qty (MOQ):	70 EA
NSN:	5305-00-576-2812
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS335CPA7-5 Specifications

Thread Direction:Right-handThread Length:0.448 Inches Minimum And 1.062 Inches MaximumFastener Length:1.015 Inches Minimum And 1.062 Inches MaximumHead Style:Flat CountersunkHead Dlameter:0.625 Inches Minimum And 0.635 Inches MaximumGrip Diameter:0.3108 Inches Minimum And 0.3117 Inches MaximumInternal Drive Style:0.535 Recess Type 1Nominal Thread Diameter:0.312 Inches0.312 Inches0.3120 Inches NominalThread Quantity Per Inch:24Vinces Strength:16000 Pounds Per Square InchHardess Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:3c.0 Microinches GripMaterial Document AndMils-5626 Mil Spec 1st Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-s6039 Mil Spec 3rd Material Response Overall Or Mils-6039 Mil Spec 4th Material Response Overall Or Mils-s6039 Mil Spec 3rd Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-s6039 Mil Spec 3rd Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-s6039 Mil Spec 3rd Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-s6039 Mil Spec 3rd Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-s6039 Mil Spec 3rd Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-s6039 Mil Spec 3rd Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-s6039 Mil Spec 3rd Material Response Overall Or Mils-5009 Mil Spec 2nd Material Response Overall Or Mils-s6039 Mil	Thread Class:	3a
Thread Length:0.448 Inches Minimum And 1.062 Inches MaximumFastener Length:1.015 Inches Minimum And 1.062 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.625 Inches Minimum And 0.635 Inches MaximumOne:0.3108 Inches Minimum And 0.635 Inches MaximumGrip Diameter:0.3108 Inches Minimum And 0.3117 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.312 InchesOniminal Thread Diameter:0.312 InchesOsto Inches Nominal10000 Pouds Per Square InchHardness Rating:0.500 Inches NominalCountersink Angle:0.00 Degrees Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:0.00 Degrees Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 87350 Stell Spee 3rd Material Response Overall Or Mil-s-6098 Mil Spee 4th Material Response Overall Or Mil-s-6049 Mil Spee 5th Material Response Overall Or Mil-s-6049		
Fastener Length:1.015 Inches Minimum And 1.062 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.625 Inches Minimum And 0.635 Inches MaximumGrip Diameter:0.3108 Inches Minimum And 0.3117 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.312 Inches0.520 Inches Minimum And 0.3117 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.312 Inches0.500 Inches NominalThread Quantity Per Inch:244Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.6.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mils-S626 Mil Spec 1st Material Response Overall Or Mils-S000 Mil Spec 2nd Material Response Overall Or Mils-6088 Mil Spec 4th Material Response Overall Or Mils-6049 Mil Spec 5th Material Response Overall Or Mils-6049 Mil Spec 3th Material Response Overall Or Material Response Overall Or Mils-6098 Mil Spec 4th Material Response Overall Or Mils-6049 Mil Spec 5th Material Response Overall Or Mils-6049 Mil Spec 3th Material Response Overall Or Mils-6049 Mil Spec 3th Material Response Overal		-
Head Style:Flat CountersunkHead Diameter:0.625 Inches Minimum And 0.635 Inches MaximumGrip Diameter:0.3108 Inches Minimum And 0.3117 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.312 InchesGrip Length:0.500 Inches NominalThread Quantity Per Inch:24Monimum Tensile Strength:0.6000 Pounds Per Square InchGolo De Duds Per Square Inch36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Materi	-	
Head Diameter:0.625 Inches Minimum And 0.635 Inches MaximumGrip Diameter:0.3108 Inches Minimum And 0.3117 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.312 InchesGrip Length:0.500 Inches NominalThread Quantity Per Inch:2Monimum Tensile Strength:0.6000 Pounds Per Square Inch36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-6008 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overal	-	
Grip Dameter:0.3108 Inches Minimu And 0.3117 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.312 Inches0.312 Inches0.310 Inches NominalGrip Length:0.500 Inches NominalThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.60.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8750 Overall Or Mil-s-6208 Mil Spec 4th Material Response Overall Or Mil-s-6308 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Mat	-	
Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.312 InchesGrip Length:0.500 Inches NominalThread Quantity Per Inch:2Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6043 Figse Camp 4140 Chromate OverallSurface Treatment:cadmium Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6043 Figse Spec All Treatment Response Overall OverallSurface Treatment Document And Classification:unf		
Nominal Thread Diameter:0.312 InchesGrip Length:0.500 Inches NominalThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Response Soverall Or Mil-s-6049 Mil Spec 5th Material Response OverallThread Series Designator:Unf		
Grip Length:0.500 Inches NominalThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OveralMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Response OverallMaterial Series Designator:Unf	-	
Thread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallMaterial Response Overall Or Mil-s-6098 Mil Spec StoreallMaterial Response OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallMaterial Response Overall Or Mil-s-6098 Mil Spec StoreallMaterial Response OverallMaterial Response Overall Or Mil-s-6098 Mil Spec StoreallMaterial Response Overall And Chromate OverallMaterial Response Ov		
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallMaterial Response Treatment Document And Classification:Unf		
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:cadmium Overall And Chromate OverallQr-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallQr-p-416,ty 2,cl 3 Fed Spec All Treatment Response OverallThread Series Designator:Unf	•	
Countersink Angle:100.0 Degrees MinimumSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallThread Series Designator:Unf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallThread Series Designator:Unf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallThread Series Designator:Unf	Countersink Angle:	100.0 Degrees Minimum
Material:OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Overall And Chromate OverallDifUnf	Surface Finish:	32.0 Microinches Grip
Classification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallThread Series Designator:Unf	Material:	
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Chromate Overall Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf	Material Document And	
Surface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses OverallThread Series Designator:Unf	Classification:	Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Specification/standard Data: 80205-nas335 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas335 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/close+tolerance+screws/NAS335CPA7-5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.