

## **P/N NAS336C13**

### **Description**

Fastener Length: 1-31/64", Thread: 3/8-24, Head Width: 7/32", Thread Length: 41/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS336C13
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-382-8967
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486. Bolts nuts Or Screws. Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS336C13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.641 Inches Nominal
Fastener Length:	1.438 Inches Minimum And 1.484 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.752 Inches Minimum And 0.762 Inches Maximum
Grip Diameter:	0.3733 Inches Minimum And 0.3742 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.812 Inches Nominal
Width Across Flats:	0.2197 Inches Minimum And 0.2217 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	100.0 Degrees Nominal
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.250 Inches Nominal First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-8844 Mil Spec 2nd Material Response Overall Or Ams 6414 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Grip And Chromate Grip
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Grip
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas336 Professional/industrial Association Standard

## **How to Order**

