

Description

Length: 1-23/64", Thread: 3/8-24, Head Width: 7/32", Thread Length: 43/64", NAS336 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS336CA12 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-314-6755 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NAS336CA12



P/N NAS336CA12 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.615 Inches Minimum And 0.682 Inches Maximum |
| Fastener Length: | 1.313 Inches Minimum And 1.360 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.752 Inches Minimum And 0.762 Inches Maximum |
| Grip Diameter: | 0.3733 Inches Minimum And 0.3742 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.678 Inches Minimum And 0.698 Inches Maximum |
| Width Across Flats: | 0.220 Inches Minimum And 0.222 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Surface Finish: | 32.0 Microinches Grip |
| Material: | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas336 Professional/industrial Association Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS336CA12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.