

Description

Fastener Length: 63/64", Thread: 3/8-24, Head Width: 7/32", Thread Length: 41/64", NAS336 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS336CA7
Minimum Qty (MOQ):	1
NSN:	5305-00-971-7467
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS336CA7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.631 Inches Minimum And 0.651 Inches Maximum
Fastener Length:	0.952 Inches Minimum And 0.999 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.752 Inches Minimum And 0.762 Inches Maximum
Grip Diameter:	0.3733 Inches Minimum And 0.3742 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Width Across Flats:	0.220 Inches Minimum And 0.222 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas336 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS336CA7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.