

P/N NAS336CP23

Description

Fastener Length: 2-31/64", Thread: 3/8-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS336CP23

Minimum Qty (MOQ): 1 EA

NSN: 5305-00-579-1266

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS336CP23 Specifications

3a
Right-hand
0.558 Inches Minimum
2.437 Inches Minimum And 2.484 Inches Maximum
Flat Countersunk
0.752 Inches Minimum And 0.762 Inches Maximum
0.3733 Inches Minimum And 0.3742 Inches Maximum
0.106 Inches Nominal First Hole
Cross Recess Type 1
0.375 Inches
1.812 Inches Nominal
24
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
100.0 Degrees Nominal
2.250 Inches Nominal First Hole
32.0 Microinches Top Of Head
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Unf
80205-nas336 Professional/industrial Association Standard

How to Order

