

Description

Fastener Length: 2-63/64", Thread: 5/8-18, Thread Length: 63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS340CPA27 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-056-0172 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS340CPA27 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.927 Inches Minimum And 0.994 Inches Maximum |
| Fastener Length: | 2.999 Inches Minimum And 3.046 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 1.262 Inches Minimum And 1.272 Inches Maximum |
| Grip Diameter: | 0.6230 Inches Minimum And 0.6240 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.625 Inches |
| Grip Length: | 2.052 Inches Minimum And 2.072 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Countersink Angle: | 100.0 Degrees Nominal |
| Surface Finish: | 32.0 Microinches Grip |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas340 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS340CPA27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.