

Description

length: 3/8", thread: 10-32, 100°, oval recessed head machine screw - chromium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS38710326P |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-182-9294 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS387-1032-6P Specifications

| | |
|-------------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.292 Inches Minimum And 0.305 Inches Maximum |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Oval Countersunk |
| Head Diameter: | 0.372 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel |
| Screw Surface Treatment: | Chromium |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas387 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS387-1032-6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.