

## P/N NAS387-632-12

### **Description**

Fastener Length: 3/4", Thread: 6-32, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS38763212

Minimum Qty (MOQ): 15 EA

NSN: 5305-00-282-9140

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS387-632-12 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Style:	Oval Countersunk
Head Diameter:	0.268 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS387-632-12">https://military-fasteners.com/screws/machine+screws/NAS387-632-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NAS387-632-12">https://military-fasteners.com/screws/machine+screws/NAS387-632-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NAS387-632-12">https://military-fasteners.com/screws/machine+screws/NAS387-632-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/nasa87-632-12">https://military-fasteners.com/screws/nasa87-632-12</a> and selecting the quantity you want <a href="https://military-fasteners.com/screws/nasa87-632-12">https://military-fasteners.com/screws/nasa87-632-12</a> and selecting the property of the pro