

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS3881018P
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-012-8232
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS388-10-18P Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.125 Inches Minimum
Fastener Length:	1.125 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.359 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 1010 Or Steel Comp 1015 Or Steel Comp 1016 Or Steel Comp 1018 Or Steel Comp 1019 Or Steel Comp 1020
Screw Material Document And Classification:	Astm A108 Assn Std All Material Responses
Screw Surface Treatment:	Cadmium Or Zinc
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 2s Style
Departure From Cited Designator:	As Modified By Fastern Lg

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS388-10-18P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.