

P/N NAS388-6-7

Description

Fastener Length: 7/16", Thread: 6-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS38867
Minimum Qty (MOQ): 10 EA

NSN: 5305-01-185-3625

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N NAS388-6-7 Specifications

| Thread Class: | 2a |
|---|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.293 Inches Minimum And 0.307 Inches Maximum |
| Fastener Length: | 0.438 Inches Nominal |
| Head Style: | Oval Countersunk |
| Head Diameter: | 0.257 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| lii Part Name Assigned By Controlling Agency: | Navy Special Project |
| Screw Material: | Steel |
| Screw Surface Treatment: | Chromate Or Cadmium |
| Thread Series Designator: | Unc |
| Specification/standard Data: | 80205-nas388 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS388-6-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.