

**Description**

length: 0.62", pulley guard pin, type k, cadmium plated steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS427K10
Minimum Qty (MOQ):	10
NSN:	5315-00-282-0287
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N NAS427K10 Specifications

<b>Fastener Length:</b>	0.901 Inches Minimum And 0.931 Inches Maximum
<b>Head Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Diameter:</b>	0.180 Inches Minimum And 0.190 Inches Maximum
<b>Grip Length:</b>	0.620 Inches Minimum And 0.650 Inches Maximum
<b>Hardness Rating:</b>	47.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 1095 Overall
<b>Material Document And Classification:</b>	Mil-s-7947 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Style Designator:</b>	Spring

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/NAS427K10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.