

Description

length: 1.12", pulley guard, type k, cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS427K18
Minimum Qty (MOQ):	10
NSN:	5315-00-597-1543
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N NAS427K18 Specifications

Fastener Length:	1.411 Inches Minimum And 1.421 Inches Maximum
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Diameter:	0.180 Inches Minimum And 0.190 Inches Maximum
Grip Length:	1.120 Inches Minimum And 1.150 Inches Maximum
Hardness Rating:	47.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Material:	Steel Comp 1095 Overall
Material Document And Classification:	Mil-s-7947 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Spring
Specification/standard Data:	80205-nas427 Professional/industrial Association Standard

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/NAS427K18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.