

## **P/N NAS427K34**

### **Description**

length: 2.12", pulley guard pin, type k, cadmium plated steel

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS427K34

Minimum Qty (MOQ): 10

NSN: 5315-00-598-2803

ECCN: EAR99

National Motor Freight: 094380, Cotter Pins / Spring Cotters Iron









<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS427K34 Specifications**

Fastener Length:	2.401 Inches Minimum And 2.431 Inches Maximum
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Diameter:	0.180 Inches Minimum And 0.190 Inches Maximum
Grip Length:	2.120 Inches Minimum And 2.150 Inches Maximum
Hardness Rating:	47.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Material:	Steel Comp 1095 Overall
Material Document And Classification:	Mil-s-7947 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Spring

## **How to Order**

Order this spring pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/spring+pins/NAS427K34">https://military-fasteners.com/pins/spring+pins/NAS427K34</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.