

Description

length: 0.38", pulley guard pin, type k, cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS427K6
Minimum Qty (MOQ):	5
NSN:	5315-00-514-0445
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N NAS427K6 Specifications

Fastener Length:	0.661 Inches Minimum And 0.691 Inches Maximum
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Diameter:	0.180 Inches Minimum And 0.190 Inches Maximum
Grip Length:	0.380 Inches Minimum And 0.410 Inches Maximum
Hardness Rating:	47.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall
Material:	Steel Comp 1095 Overall
Material Document And Classification:	Mil-s-7947 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Spring

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/NAS427K6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.