

Description

length: 0.38", pulley guard pin, type k, cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS427K6 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5315-00-514-0445 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



P/N NAS427K6 Specifications

| | |
|----------------------------------------------|---------------------------------------------------------------------|
| Fastener Length: | 0.661 Inches Minimum And 0.691 Inches Maximum |
| Head Diameter: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Diameter: | 0.180 Inches Minimum And 0.190 Inches Maximum |
| Grip Length: | 0.380 Inches Minimum And 0.410 Inches Maximum |
| Hardness Rating: | 47.0 Rockwell C Minimum Overall And 52.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 1095 Overall |
| Material Document And Classification: | Mil-s-7947 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Style Designator: | Spring |

How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/NAS427K6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.