



Military-Fasteners.com

P/N NAS428-3A26

Description

Fastener Length: 2-3/4", Thread: 10-32, Thread Length: 2-11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4283A26
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-616-2353
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS428-3A26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.688 Inches Minimum
Fastener Length:	2.750 Inches Nominal
Head Style:	Crowned Hexagon
Head Height:	0.109 Inches Nominal
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.062 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Special Features:	Adjusting Slot Thd End
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas428 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428-3A26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.