

Description

Fastener Length: 4-13/16", Thread: 1/4-28, Thread Length: 4-25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS428446
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-431-1135
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS428-4-46 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	4.688 Inches Minimum And 4.781 Inches Maximum
Fastener Length:	4.750 Inches Minimum And 4.812 Inches Maximum
Head Style:	Crowned Hexagon
Head Height:	0.141 Inches Nominal
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas428 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428-4-46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.