

Description

length: 1-1/4", thread: 1/4-28, crowned hex head, cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS4284A12 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-535-3722 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS428-4A12 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.688 Inches Minimum And 1.719 Inches Maximum |
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Crowned Hexagon |
| Head Height: | 0.141 Inches Nominal |
| Width Between Flats: | 0.438 Inches Nominal |
| End Item Identification: | E Fwd Fuselag |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.031 Inches Minimum And 0.062 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Part Name Assigned By Controlling Agency: | Bolt,machine,125,000 Psi - Crowned Hexagon Head,adjusting |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Mil-b-6812 Mil Spec All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428-4A12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.