

P/N NAS428-5A10

Description

Fastener Length: 1-1/16", Thread: 1/4-24, Thread Length: "

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS4285A10

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-561-0787

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS428-5A10 Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.870 Inches Nominal |
| Fastener Length: | 1.000 Inches Minimum And 1.062 Inches Maximum |
| Head Style: | Crowned Hexagon |
| Head Height: | 0.162 Inches Minimum And 0.182 Inches Maximum |
| Width Between Flats: | 0.490 Inches Minimum And 0.502 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.031 Inches Minimum And 0.062 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| lii Part Name Assigned By Controlling Agency: | Navy Special Project |
| Material: | Steel Comp 4037 Overall And Steel Comp 4130 Overall And Steel Comp 8630 Overall And Steel Comp 8735 Overall And Steel Comp 8740 Overall And Steel Comp 4140 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS428-5A10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.