

P/N NAS428-5A10

Military-Fasteners.com

Description

Fastener Length: 1-1/16", Thread: 1/4-24, Thread Length: "

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS4285A10
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-561-0787
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS428-5A10 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.870 Inches Nominal
Fastener Length:	1.000 Inches Minimum And 1.062 Inches Maximum
Head Style:	Crowned Hexagon
Head Height:	0.162 Inches Minimum And 0.182 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
lii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Steel Comp 4037 Overall And Steel Comp 4130 Overall And Steel Comp 8630 Overall And Steel Comp 8735 Overall And Steel Comp 8740 Overall And Steel Comp 4140 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS428-5A10</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.