



Military-Fasteners.com

P/N NAS428-5A26

Description

Fastener Length: 2-3/4", Thread: 1/4-24, Thread Length: 2-23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS4285A26
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-133-0139
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS428-5A26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.688 Inches Minimum And 2.721 Inches Maximum
Fastener Length:	2.750 Inches Minimum And 2.752 Inches Maximum
Head Style:	Crowned Hexagon
Head Height:	0.162 Inches Minimum And 0.182 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas428 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428-5A26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.