

Description

Fastener Length: 3/4", Thread: 1/4-24, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS4285A6 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-286-1349 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS428-5A6 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.688 Inches Minimum And 0.719 Inches Maximum |
| Fastener Length: | 0.750 Inches Nominal |
| Head Style: | Crowned Hexagon |
| Head Height: | 0.172 Inches Nominal |
| Width Between Flats: | 0.500 Inches Nominal |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.031 Inches Minimum And 0.062 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Mil-b-6812 Mil Spec All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428-5A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.