

P/N NAS428-6-22

Military-Fasteners.com

Description

Fastener Length: 2-1/4", Thread: 3/8-24, Thread Length: 2-7/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS428622
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-531-0419
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS428-6-22 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	2.188 Inches Minimum And 2.219 Inches Maximum
Fastener Length:	2.250 Inches Nominal
Head Style:	Crowned Hexagon
Head Height:	0.203 Inches Nominal
Width Between Flats:	0.563 Inches Nominal
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas428 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS428-6-22</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.