

P/N NAS428-6A22

Description

Fastener Length: 3-3/4", Thread: 3/8-24, Thread Length: 2-15/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS4286A22

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-527-5477

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS428-6A22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.438 Inches Minimum And 2.469 Inches Maximum
Fastener Length:	3.750 Inches Nominal
Head Style:	Crowned Hexagon
Head Height:	0.203 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
End Item Identification:	E Fwd Fuslag
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,machine,125,000 Psi-crowned Hexagon Head,adjusting
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type Ii,class2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS428-6A22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.