

**Description**

Fastener Length: 3-3/4", Thread: 3/8-24, Thread Length: 2-15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS4286A22
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-527-5477
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS428-6A22 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	2.438 Inches Minimum And 2.469 Inches Maximum
<b>Fastener Length:</b>	3.750 Inches Nominal
<b>Head Style:</b>	Crowned Hexagon
<b>Head Height:</b>	0.203 Inches Nominal
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.565 Inches Maximum
<b>End Item Identification:</b>	E Fwd Fuslag
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.031 Inches Minimum And 0.062 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,machine,125,000 Psi-crowned Hexagon Head,adjusting
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-b-6812 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type II,class2 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428-6A22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.