

Description


Fastener Length: 1-1/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 31/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS428H310
Minimum Qty (MOQ):	5
NSN:	5306-00-207-4591
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS428H3-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.938 Inches Minimum And 0.969 Inches Maximum
Fastener Length:	1.000 Inches Minimum And 1.062 Inches Maximum
Head Style:	Crowned Hexagon
Head Height:	0.109 Inches Nominal
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas428 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428H3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.